

Copper Brazing Fittings

• Copper fittings can be used for LPG, NG, SNG, biomethane and other non-aggressive gas (nitrogen, air..) installations and also for potable water, heating and cooling installations.



- 1 European quality copper
- 3 Diameter marking for better identification

Service pressure up to 25bar depending on brazing material used. Large range: from 6mm to 108mm In conformity with EN1254-1

Code	Inlet code	Inlet connection	Outlet code	Outlet connection	Service pressure (bar)	Observation
NUT + NOZZLE for BRAZING						
PP04508			K3C	PIPE-8-CTS		
PP04510]		K3D	PIPE-10-CTS		1
PP04512	N6A	NUT-M20x1,5RH	K3E	PIPE-12-CTS		
PP04515		,	K3G	PIPE-15-CTS	00	with rubber
PP04520	1 i		K3F	PIPE-14-CTS		
PP08312			K3E	PIPE-12-CTS	20	seal
PP08314] i		K3F	PIPE-14-CTS		
PP08316	N5N	NUT-G3/4RH-NF-LINE	K3J	PIPE-16-CTS		
PP08318] i		K3K	PIPE-18-CTS		
PP83022] [K3L	PIPE-22-CTS		
PP15811			K3F	PIPE-14-CTS		
PP15815	N5D	NUT-G1/2RH-NF	K3G	PIPE-15-CTS		
P037400]		K3J	PIPE-16-CTS	4.75	with fiber / resin
PP38901			K3L	PIPE-22-CTS	1.75	seal
PP38902] -	NUT-G1"RH-NF-LINE	K3M	PIPE-28-CTS		
PP18//08	1		K3M	PIPE-28_CTS	1	1

	Code	Suitable for:		Outlet code	Outlet connection	Service pressure (bar)	Observation]
		Inlet code	Inlet connection	Outlot code	Outlet confidential	Service pressure (bar)	Observation	
	NOZZLE for BRAZING							
	P410108			K3C	PIPE-8-CTS			1
	P410110		AULT MOD 4 EDIL	K3D	PIPE-10-CTS			L
	P410112	NOA	NUT-WIZUXT, OHT	K3E	PIPE-12-CTS			П
_	P410114			K3F	PIPE-14-CTS	20	With rubber seal	۲.
	P840614			K3F	PIPE-14-CTS	20	Willi Tubber Sear	
	P840615	N5N	NUT-G3/4RH-NF-LINE	K3G	PIPE-15-CTS			
	P840616	NICH	NU1-U3/4n∏-NF-LINE	K3J	PIPE-16-CTS			
	P840618			K3K	PIPE-18-CTS			

Code	Inlet code	Inlet connection	Outlet code	Outlet connection	Service pressure (bar)	
	MALE for BRAZING					
P005107			K3C	PIPE-8-CTS		
P005111	E6B	MAL-M20x1.5RH	K3D	PIPE-10-CTS		
P005113	LOD	IVIAL-IVIZUXT, Shri	K3E	PIPE-12-CTS	20	
P005115			K3F	PIPE-14-CTS	20	
P004211	L2A	MAL-NF21.7LH	K3E	PIPE-12-CTS		
P004215	LZA	WAL-NFZ1,7LFI	K3F	PIPE-14-CTS		

Brass Brazing Fittings

- Brass fittings can be used for LPG, NG, SNG, biomethane and other non-aggressive gas (nitrogen, air ...)
- In conformity with EN12164 and 12165 standards.
- For all available dimensions please contact us.

Code	Internal diameter			
Copper brazing 90° elbow Female Female - 5090				
090012	12			
090014	14			
090015	15			
090016	16			
090018	18			
090022	22			
090028	28			
090032	32			
Copper brazing equal tee Female Female Female - 5130				
130012	12			
130014	14			
130015	15			
130016	16			
130018	18			
130018 130022	18 22			
130022	22			

Code	Internal diameter			
Copper brazing reduction tee Female Female Female - 5130R				
131535	15-12-15			
131837	18-12-18			
132259	22-15-22			
132900	28-22-28			
133302	32-28-32			
Copper brazing reduction Female Female - 5240				
240162	15-12			
240192	18-12			
240195	18-15			
240235	22-15			
240298	28-18			
240302	28-22			
240348	32-28			
Copper brazing sleev	e Female Female - 5270			
270012	12			
270015	15			
270018	18			
270022	22			
270028	28			
270032	32			



