

Copper Brazing Fittings

• Copper fittings can be used for LPG, NG, SNG, biomethane and other non-aggressive gas (nitrogen, air..) installations and also for potable water, heating and cooling installations.



- 1 European quality copper
- 3 Diameter marking for better identification

Service pressure up to 25bar depending on brazing material used. Large range: from 6mm to 108mm In conformity with EN1254-1

Code	Inlet code	Inlet connection	Outlet code	Outlet connection	Service pressure (bar)	Observation	
NUT + NOZZLE for BRAZING							
PP04508			K3C	PIPE-8-CTS			
PP04510]		K3D	PIPE-10-CTS			
PP04512	N6A	NUT-M20x1,5RH	K3E	PIPE-12-CTS			
PP04515			K3G	PIPE-15-CTS			
PP04520			K3F	PIPE-14-CTS	20	with rubber	
PP08312			K3E	PIPE-12-CTS	20	seal	
PP08314			K3F	PIPE-14-CTS			
PP08316	N5N	NUT-G3/4RH-NF-LINE	K3J	PIPE-16-CTS			
PP08318]		K3K	PIPE-18-CTS			
PP83022] [K3L	PIPE-22-CTS			
PP15811			K3F	PIPE-14-CTS			
PP15815	N5D	NUT-G1/2RH-NF	K3G	PIPE-15-CTS			
P037400]		K3J	PIPE-16-CTS	1 75	with fiber / resin	
PP38901			K3L	PIPE-22-CTS	1.75	seal	
PP38902] -	NUT-G1"RH-NF-LINE	K3M	PIPE-28-CTS			
PP18408	1 i		K3M	PIPE-28-CTS			

Code	Suitable for:		Outlet code	Outlet connection	Coming programs (bor)	Observation
Code	Inlet code	Inlet connection	Ouliet code	Outlet connection	Service pressure (bar)	Observation
NOZZLE for BRAZING						
P410108			K3C	PIPE-8-CTS		
P410110	N6A	NUT-M20x1,5RH	K3D	PIPE-10-CTS		
P410112			K3E	PIPE-12-CTS		
P410114			K3F	PIPE-14-CTS	20	With rubber seal
P840614			K3F	PIPE-14-CTS	20	Willi Tubber Sea
P840615	l		K3G	PIPE-15-CTS		
P840616	NSN	NUT-G3/4KH-NF-LINE	K3J	PIPE-16-CTS		
P840618			K3K	PIPE-18-CTS		

Code	Inlet code	Inlet connection	Outlet code	Outlet connection	Service pressure (bar)
MALE for BRAZING					
P005107			K3C	PIPE-8-CTS	
P005111	E6B	MAL-M20x1.5RH	K3D	PIPE-10-CTS	
P005113		IVIAL-IVIZUXT, Shri	K3E	PIPE-12-CTS	20
P005115				K3F	PIPE-14-CTS
P004211	- 12Δ	MAL-NF21.7LH	K3E	PIPE-12-CTS	
P004215		LZA WIAL-NFZ1,7LH	K3F	PIPE-14-CTS	

Brass Brazing Fittings

- Brass fittings can be used for LPG, NG, SNG, biomethane and other non-aggressive gas (nitrogen, air ...)
- In conformity with EN12164 and 12165 standards.
- For all available dimensions please contact us.

Code	Internal diameter			
Copper brazing 90° elbow Female Female - 5090				
090012	12			
090014	14			
090015	15			
090016	16			
090018	18			
090022	22			
090028	28			
090032	32			
Copper brazing equal tee Female Female Female - 5130				
130012	12			
130014	14			
130015	15			
130016	16			
130018	18			
130022	22			
130022 130028				
	22			

Other sizes available upon reque	est	
Code	Internal diameter	
Copper brazing reduction tee	Female Female - 5130R	
131535	15-12-15	
131837	18-12-18	
132259	22-15-22	
132900	28-22-28	
133302	32-28-32	
Copper brazing reduct	ion Female Female - 5240	
240162	15-12	
240192	18-12	
240195	18-15	
240235	22-15	
240298	28-18	
240302	28-22	
240348	32-28	
Copper brazing sleev	re Female Female - 5270	
270012	12	
270015	15	
270018	18	
270022	22	
270028 28		
270032	32	



